

## CLAIMS

I claim:

1. A party display apparatus comprising:  
an elongated rod having an upper end and a lower end;  
a canopy having an upper surface and a lower surface, a coupler  
being attached to said lower surface for selectively coupling  
said upper end of said rod to said canopy; and  
a plurality of fastening members being attached to said upper  
surface of said canopy for selectively fastening objects to said  
canopy.
2. The party display apparatus of claim 1, further including a  
base being attached to said lower end.
3. The party display apparatus of claim 2, wherein said base  
comprises a handle.
4. The party display apparatus of claim 3, wherein said handle is  
arcuate and generally has a J-shape.
5. The party display apparatus of claim 1, wherein said base  
comprises a panel, said lower end of said rod being attached to and  
extending upwardly from a top side of said panel such that said rod is  
orientated generally perpendicular to a plane of said panel.
6. The party display apparatus of claim 1, wherein said upper  
end of said rod is threaded, said coupler comprising a threaded female  
socket for threadably coupling with said upper end.

7. The party display apparatus of claim 1, wherein said canopy comprising a substantially rigid material.

8. The party display apparatus of claim 7, wherein said plurality of fastening members substantially covers said upper surface of said canopy.

9. The party display apparatus of claim 8, wherein each of said plurality of fastening members comprises a clip biased downwardly toward said upper surface.

10. The party display apparatus of claim 1, wherein said plurality of fastening member substantiallys covers said upper surface of said canopy.

11. The party display apparatus of claim 12, wherein each of said plurality of fastening members comprises a clip biased downwardly toward said upper surface.

13. A party display apparatus comprising:  
an elongated rod having an upper end and a lower end, a base being attached to said lower end, said upper end being threaded, said base comprising an arcuate handle generally having a J-shape;  
a canopy having an upper surface and a lower surface, a coupler being attached to said lower surface for selectively coupling said upper end of said rod to said canopy, said coupler comprising a threaded female socket for threadably coupling with said upper end, said canopy comprising a substantially rigid material; and

a plurality of fastening members being attached to said upper surface of said canopy for selectively fastening objects to said canopy, said plurality of fastening members substantially covering said upper surface of said canopy, each of said plurality of fastening members comprising a clip biased downwardly toward said upper surface.